

7769 95th Street South Cottage Grove, MN

SAFETY DATA SHEET

Revision Date: 7/29/2015

Emergency Phone: 1-800-535-5053 (Infotrac)

Section 1: Identification

Product Name: Klear-Vu Concentrate Code: 98PKC00

Chemical Type: Liquid Manufacturer/Supplier:

Innovative Chemical Corporation

7769 95th Street South Cottage Grove, MN 55016

651-649-1762

Section 2: Hazard(s) Identification

OSHA/HCS status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture: SKIN CORROSION/IRRITATION - Category 2

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

Label elements

Signal word: Danger

Hazard statements: Causes serious eye irritation.

Causes skin irritation.

Flammable.



Precautionary Statements

Prevention: Wear protective gloves: < 1 hour (breakthrough time): disposable vinyl. Wear eye or face

protection: Recommended: splash goggles. Wash hands thoroughly after handling.

Response: IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash

contaminated clothing before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage: Not applicable.

Disposal: Not applicable.

Hazards not None known.

otherwise classified:

Section 3: Composition/Information on Ingredients

Substance or mixture: Mixture
Other means of identification: Not available.

CAS number/other identifiers

CAS number: Not applicable.

Hazardous Components		
Chemical Name	%weight	CAS
2-Butoxyethanol; Ethylene glycol monobutyl ether	5-10	111-76-2
ammonia	2-5	1336-21-6
isopropanol	20-30	67-63-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation. There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational limits, if available are listed in Section 8.

Section 4: First-Aid Measures

Description of first aid measures

Eyes	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for
	and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if
	breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained
	personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get
	medical attention if adverse health effects persist or are severe. If unconscious, place in recovery
	position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as
	a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may
	be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to
	rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly
	before reuse.
Ingestion	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a
	position comfortable for breathing. If material has been swallowed and the exposed person is conscious,
	give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be
	dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs,
	the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse
	health effects persist or are severe. Never give anything by mouth to an unconscious person. If
	unconscious, place in recovery position and get medical attention immediately. Maintain an open
	airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact	Causes serious eye irritation.	
Inhalation	No known significant effects or critical hazards.	
Skin contact	Causes skin irritation.	
Ingestion No known significant effects or critical hazards.		

Over-exposure signs/symptoms

Eye contact	Adverse symptoms may include the following: pain or irritation, watering, redness	
Inhalation	No specific data.	
Skin contact	Adverse symptoms may include the following: irritation, redness	
Ingestion	No specific data.	

Indication of any immediate medical attention needed

Notes to Physician	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed	
	person may need to be kept under medical surveillance for 48 hours.	
Specific treatment	No specific treatment.	
Protection of first- No action shall be taken involving any personal risk or without suitable training. It may be dangerous to		
aiders	the person providing aid to give mouth-to-mouth resuscitation.	

See toxicological information (Section 11)

Section 5: Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may
Hazardous thermal decomposition products	Decomposition products may include the following materials: carbon dioxide,
	carbon monoxide, nitrogen oxides, sulfur oxides, metal oxide/oxides
Protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the
	incident if there is a fire. No action shall be taken involving any personal risk or
	without suitable training.
Protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained
	breathing apparatus (SCBA) with a full face-piece operated in positive pressure
	mode.

Section 6: Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate	
	surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not	
	touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate	
	ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate	
	personal protective equipment.	
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information in	
	Section 8 on suitable and unsuitable materials. See also the information in "For	
	nonemergency personnel".	
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and	
	sewers. Inform the relevant authorities if the product has caused environmental pollution	
	(sewers, waterways, soil or air).	

Methods and material for containment and cleaning up

Small spill	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7: Handling and Storage

Precautions for safe handling

Protective measures	Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational	Eating, drinking and smoking should be prohibited in areas where this material is handled,
hygiene	stored and processed. Workers should wash hands and face before eating, drinking and
	smoking. Remove contaminated clothing and protective equipment before entering eating
	areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage	Store in accordance with local regulations. Store in original container protected from direct
including any incompatibilities	sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see
	Section 10) and food and drink. Keep container tightly closed and sealed until ready for use.
	Containers that have been opened must be carefully resealed and kept upright to prevent
	leakage. Do not store in unlabeled containers. Use appropriate containment to avoid
	environmental contamination.

Section 8: Exposure Controls/Personal Protection

Control parameters

Occupational exposure limits

Ingredient Name	Exposure Limits
-----------------	-----------------

2-Butoxyethanol; Ethylene glycol monobutyl ether	OSHA PEL 1989 (United States, 3/1989).
	Absorbed through skin.
	TWA: 25 ppm 8 hours.
	TWA: 120 mg/m³ 8 hours.
	NIOSH REL (United States, 10/2013).
	Absorbed through skin.
	TWA: 5 ppm 10 hours.
	TWA: 24 mg/m ³ 10 hours.
	ACGIH TLV (United States, 4/2014).
	TWA: 20 ppm 8 hours.
	OSHA PEL (United States, 2/2013).
	Absorbed through skin.
	TWA: 50 ppm 8 hours.
	TWA: 240 mg/m³ 8 hours.

Appropriate engineering	Good general ventilation should be sufficient to control worker exposure to airborne
controls	contaminants
Environmental exposure	Emissions from ventilation or work process equipment should be checked to ensure they
controls	comply with the requirements of environmental protection legislation. In some cases, fume
	scrubbers, filters or engineering modifications to the process equipment will be necessary to
	reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Respiratory	Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Eyes/Face	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Recommended: splash goggles
Hands	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. < 1 hour (breakthrough time): disposable vinyl

Skin/Body

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Section 9: Physical and Chemical Properties

Physical state

Liquid Blue

Color Odor

Alcohol/Ammonia

Odor threshold

Not available

рΗ

10.5

Melting Point

Not available Not available

Boiling Point Flash Point

Closed cup: >100°C (>212°F)

Evaporation rate

Not available

Flammability (solid, Not available

gas)

Lower and upper

Not available

explosive

(flammable) limits

Vapor pressure Vapor density

Not available Not available

Relative density

Solubility

Easily soluble in cold and hot water.

Partition

Not available

coefficient: n-

octanol/water

Auto-ignition Not available

temperature

Decomposition

Not available

temperature

Viscosity Not available

Section 10: Stability and Reactivity

Reactivity:

No specific test data related to reactivity available for this product or its ingredients.

Chemical stability:

The product is stable.

Possibility of hazardous

Under normal conditions of storage and use, hazardous reactions will not occur.

reactions:

Conditions to avoid: Incompatible materials: No specific data. No specific data.

Hazardous decomposition

Under normal conditions of storage and use, hazardous decomposition products should

products:

not be produced.

Section 11: Toxicological Information

Acute toxicity

Ingredient name	Result	Species	Dose	Exposure
2-Butoxyethanol; Ethylene glycol monobutyl	LC50 Inhalation Gas	Rat	450 ppm	4 hours
ether				
	LD50 Dermal	Rabbit	220 mg/kg	-
	LD50 Oral	Rat	250 mg/kg	-
ammonia	LD50 Oral	Rat	350 mg/kg	-

Irritation/Corrosion

Ingredient name	Result	Species	Score	Exposure	Observation
2-Butoxyethanol; Ethylene	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-
glycol monobutyl ether				milligrams	
	Eyes - Severe irritant	Rabbit	-	100	-
				milligrams	
	Skin - Mild irritant	Rabbit	-	500	-
				milligrams	
ammonia	Eyes - Severe irritant	Rabbit	-	250	
				Micrograms	
	Eyes - Severe irritant	Rabbit	-	0.5 min 1	
				milligrams	

Sensitization

Not available

Mutagenicity

Not available

Carcinogenicity

Not available

Product/Ingredient name	OSHA	IARC	NTP
2-Butoxyethanol; Ethylene	-	3	-
glycol monobutyl ether			

Reproductive toxicity

Not available

Teratogenicity

Not available

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Information on the likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation

Potential acute health effects

Eye contact	Causes serious eye irritation.	
Inhalation	No known significant effects or critical hazards.	
Skin contact	Causes skin irritation.	
Ingestion	No known significant effects or critical hazards.	

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	Eye contact Adverse symptoms may include the following: pain or irritation, watering, redness		
Inhalation	Inhalation No specific data.		
Skin contact Adverse symptoms may include the following: pain or irritation, redness			
Ingestion	No specific data.		

Delayed and immediate effects and chronic effects from short and long term exposure

Short term exposure

Potential immediate effects: Not available.

Potential delayed effects: Not available.

Long term exposure

Potential immediate effects: Not available.

Potential delayed effects: Not available.

Potential chronic health effects

Not available

General:No known significant effects or critical hazards.Carcinogenicity:No known significant effects or critical hazards.Mutagencity:No known significant effects or critical hazards.Teratogenicity:No known significant effects or critical hazards.Developmental effects:No known significant effects or critical hazards.Fertility effects:No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	3006.3 mg/kg
Dermal	9353.7 mg/kg
Inhalation (vapors)	93.54 mg/l

Section 12: Ecological information

Toxicity

Ingredient name	Result	Species	Exposure
-----------------	--------	---------	----------

Klear-Vu Concentrate page 1

2-Butoxyethanol; Ethylene	Acute EC50 >1000 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
glycol monobutyl ether		Crustaceans - Crangon	
	Acute LC50 800000 μg/l Marine water	crangon	48 hours
		Fish - Menidia beryllina	
	Acute LC50 1250000 μg/l Marine water		96 hours
ammonia	Acute LC50 37 ppm Fresh water	Fish - Gambusia affinis -	96 hours
		Adult	

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-Butoxyethanol; Ethylene	0.81	-	low
glycol monobutyl ether			

Mobility in soil

Soil/water partition coefficient (Koc): Not available

Other adverse effects: No known significant effects or critical hazards.

Section 13: Disposal considerations

Waste disposal

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14: Transport information

	UN				Environment	
Regulatory info	number	Proper shipping name	Classes	PG	al hazards	Additional info

DOT Classification	Not	No.	Reportable quantity
	regulated		31397.2 lbs / 14254.3 kg
			[3842.4 gal / 14545.2 L]
			Package sizes shipped in
			quantities less than the
			product reportable
			quantity are not subject
			to the RQ (reportable
			quantity) transportation
			requirements.
TDG Classification	Not	No.	
	regulated		
Mexico	Not	No.	
Classification	regulated		
ADR/RID Class	Not	No.	
	regulated		
IMDG Class	Not	No.	
	regulated		
IATA-DGR Class	Not	No.	
	regulated		

Special precautions for user: Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to

do in the event of an accident or spillage.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code:

Not available

Section 15: Regulatory information

U.S. Federal regulations TSCA 8(a) CDR Exempt/Partial exemption: Not determined

All components are listed or exempted. Clean Water Act (CWA) 311: ammonia

Clean Air Act Section 112(b)

Hazardous Air Pollutants

(HAPs)

Not Listed

Clean Air Act Section 602 Class Not Listed

I Substances

Clean Air Act Section 602 Class Not Listed

II Substances

DEA List I Chemicals (Precursor Not Listed **Chemicals)**

DEA List II Chemicals (Essential Not Listed **Chemicals)**

SARA 302/304 No products found

SARA 304 RQ Not applicable.

SARA 311/312 Classification

Immediate (acute) health hazard

Composition/information on ingredients

					Immediate	Delayed
			Sudden		(acute)	(chronic)
			release of		health	health
Name	%	Fire hazard	pressure	Reactive	hazard	hazard
2-Butoxyethanol; Ethylene	5-10	No.	No.	No.	Yes.	No.
glycol monobutyl ether						
ammonia	2-5	No.	No.	No.	Yes.	No.

SARA 313

	Product Name	CAS number	%
Form R - Reporting	2-butoxyethanol	111-76-2	5-10
Requirements	ammonia	1336-21-6	2-5
	isopropanol	67-63-0	20-30
Supplier notification	2-butoxyethanol	111-76-2	5-10
	ammonia	1336-21-6	2-5
	isopropanol	67-63-0	20-30

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts: The following components are listed: 2-BUTOXYETHANOL; AMMONIUM HYDROXIDE

New York: The following components are listed: Ammonium hydroxide

New Jersey: The following components are listed: 2-BUTOXY ETHANOL; BUTYL CELLOSOLVE;

AMMONIUM HYDROXIDE; ETHYL ALCOHOL; ALCOHOL

Pennsylvania: The following components are listed: ETHANOL, 2-BUTOXY-; AMMONIUM HYDROXIDE

((NH4)(OH)); DENATURED ALCOHOL

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not Listed

Montreal Protocol (Annexes A, B, C, E)

Not listed

Stockholm Convention on Persistent Organic Pollutants

Not listed

Rotterdam Convention on Prior Inform Consent (PIC)

Not listed

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed

International Lists:

National Inventory

Australia All components are listed or exempted.

Canada All components are listed or exempted.

China All components are listed or exempted.

Europe Not determined.

Japan All components are listed or exempted.

Malaysia Not determined.

New ZealandAll components are listed or exempted.PhilippinesAll components are listed or exempted.Republic of KoreaAll components are listed or exempted.TaiwanAll components are listed or exempted.

Section 16: Other information

Hazardous Material


Information System (U.S.A.):



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J.J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association:



Reprinted with permission from NFFA 704-2001, Identification of the Flazarus of Iviaterials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

Classification	Justification		
Skin Corr. 2, H315	Calculation method		
Eye Dam. 2A, H319	Calculation method		

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist