

APPLAUSE

16% HIGH GLOSS HIGH SPEED FLOOR COATING



DATA SHEET

Product Description:

Applause is a unique blend of Acrylic Polymers that provides exceptional floor finish performance features- excellent resistance to dirt, scuff and black heel markings. Applause is not easily removed with aggressive cleaners. It's unique toughness enables it to outlast it's competition in a variety of applications, including excellent gloss retention where High-Speed buffing is less frequent. Applause is recommended for use on all types of resilient tile, linoleum, terazzo, quarry tile or sealed wood. Apply over appropriate floor sealer, either MVP (sealer) or Tuf Kote (high solid acrylic sealer) as directed.

Features:

- Our most economical yet versatile floor coating.
- High gloss.
- All raw materials used for production undergo a thorough quality control process before being used for manufacturing high quality products.

Directions:

1. Floor must be cleaned and free of any other floor maintenance products, either stripper or finish. If floor is old and porous, apply Tuf Kote as directed. Otherwise use Ace as directed.
2. With a clean mop or applicator, apply 2-3 coats of finish (wait for drying between coats).
3. With finish completely dry, buff with High-Speed buffer to obtain desired shine. Apply 1-2 coats of Applause to clean/dry floor.

Stripping:

1. Applause is easily removed with Hot Shot or Zap fast penetrating stripper when used as directed.
2. Always clean floor with Quantum or fresh water prior to applying sealer or finish.

Specifications:

Available In:

Color:	White	55 Gallon Pail	Item# 98PAP55
Odor:	None Added	30 Gallon Pail	Item# 98PAP30
pH:	8.7	5 Gallon Pail	Item# 98PAP05
Physical State:	Liquid	4x1 Gallon Bottles	Item# 98PAP0G

First Aid:

Inhalation: Remove to fresh air. Skin: Wash with soap and water. Eyes: Flush with water for 15 minutes. If irritation persists, consult physician. Internal: If ingested, drink large amounts of water. DO NOT induce vomiting. Seek medical attention promptly.

Storage:

Keep from freezing. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area.



**INNOVATIVE
CHEMICAL
CORPORATION**

St. Paul, MN 55016
Phone: 651-649-1762
866-472-3932
www.iccmn.com