LOW FOAM-CLEANER

Product Description:

Low foaming cleaner is ideal for use in auto scrubbers, extraction and CIP systems. This product exhibits tremendous results in removing embedded soil, grease, oils, etc. Low Foam is ideal for use in industrial and food processing plants. It is also effective in manual applications. All Natural. Contains no caustics or solvent.

Features:

Ideal for use in auto scrubbers, extraction and CIP systems. Removes embedded soil, grease, oils, etc.



Specifications:

Color: Clear
Odor: Lemon
pH: 9.5
Physical State: Liquid

Available In:

5 Gallon Pails Item# 98PLF05 30 Gallon Pails Item# 98PLF30 55 Gallon Pails Item# 98PLF55 4x1 Gallon Bottles Item# 98PLF0G

Directions:

Automatic Scrubbers: Add Low Foam after the solution tank is filled with water, not before.

- For normal cleaning, dilute one part Low Foam with 40 parts water.
- For economy, Low Foam may be diluted up to 1:60 or 1:128.
- For heavy soil, Low Foam may be diluted at 1:15 or 1:20.

For optimum economy and performance, experiment with different dilution levels (1:15 to 1:128 is recommended). Low Foam may be used on all surfaces not harmed by water: floors, walls, woodwork, marble, plastic and metal.

First Aid:

In case of contact: Skin: Flush with water. Seek medical attention if irritation persists. Eyes: Flush with large quantities of water, holding eyelids open. Seek medical attention immediately. Inhalation: Get to fresh air, seek medical attention if irritation persists. Ingestion: DO NOT induce vomiting. Drink large quantities of water. Seek medical attention.

Storage:

Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink. Use appropriate containment to avoid environmental contamination.

