HOT SHOT-CONCENTRATED BUTYL STRIPPER

Product Description:

A deep penetrating stripper formulated for the removal of multiple coats of today's detergent resistant hard sealers and finishes. This is recommended for use on resilient tile, vinyl, rubber, terazzo, quarry tile, brick and concrete.

Features:

The premier floor stripper for professional cleaners. Formulated to deep penetrate multiple coats of floor finish and seals. All raw materials used for production undergo a thorough quality control process before being used for manufacturing high quality products.



Specifications:

Color: Red

Odor: Low Odor

pH: 12 Physical State: Liquid

Available In:

5 Gallon Pails Item# 98PHS05 30 Gallon Pails Item# 98PHS30 55 Gallon Pails Item# 98PHS55 4x1 Gallon Bottles Item# 98PHS0G

Directions:

- Floor Dust mop or sweep floor area.
- -With Prepare solution in the following ratios: light build up: 16oz per gallon of water, medium build up: 21oz per gallon of water, heavy build up: 32oz per gallon of water.
- -When using on asphalt tile, first test solution in an inconspicuous area.
- -Apply liberally without flooding with mop or auto scrubber. Do not allow solution to dry. Apply more stripper solution if drying occurs too quickly.
- -Neutralize/rinse floors.

First Aid:

Inhalation: Remove to fresh air. Skin: Wash with soap and water for 15 minutes. If irritation persists, consult physician. Internal: If ingested, drink large amounts of water or milk. Seek medical attention promptly.

Storage:

Use only containers and equipment designed for alkali services. Product may be disposable in sewers if neutralized and if local regulations permit. Otherwise, send to a licensed treatment facility. Rinse empty containers before handing and disposal. In an enclosed area, ventilate in any suitable manner.

