DATA SHEET

LOW PH PRESOAK II LOW % HF

None Added

Product Description:

Less acidic version of low pH presoak. Use in tunnels or bay automatics with high pressure equipment. Loosens road film, insects, oxidative film and heavy residue often not removable by ordinary spray cleaning.

Specifications:

Color: Clear

pH: 1

Physical State: Liquid Dilution: 1:100

Available In:

55 Gallon Drums Item# 98PL255 30 Gallon Drums Item# 98PL230 05 Gallon Pails Item# 98PL205



Directions:

Odor:

As a pressure washer, dilute 1:60-1:150 with water. In foamers, dilute 1:125 with water.

First Aid:

If in eyes: Remove contact lenses and flush eyes with water for 15 minutes. If swallowed: Rinse mouth with water, spit out and rinse again. Then drink a glass of water. DO NOT induce vomiting unless instructed by medical personnel. Get immediate medical attention. If on skin: Flush thoroughly with water. In all cases, get medical attention if irritation persists.

Storage:

Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink. Use appropriate containment to avoid environmental contamination. Keep container tightly closed and sealed until ready to use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

