

MVP-18% FLOOR SEAL / FINISH

Product Description:

An acrylic non-yellowing all purpose sealer for resilient tile and concrete surfaces. MVP is especially formulated to be tough and provide good resistance to amine based strippers. Floor finishes applied over MVP can be removed without affecting the seal, adding life and cost savings to the floor maintenance program. Tuf Kote is recommended for use on all types of resilient tiles, Terrazo, Quarry tile or concrete. It is ideal for older floors that are porous.

Features:

Gives extra protection to all resilient floor surfaces. Water based and metal free. Increase performance of any acrylic finish. All raw materials used for production undergo a thorough quality control process before being used for manufacturing high quality products.



Specifications:

Color:	White
Odor:	None Added
pH:	8.7
Physical State:	Liquid

Available In:

5 Gallon Pail	Item# 98PMV05
30 Gallon Pail	Item# 98PMV30
55 Gallon Pail	Item# 98PMV55
4x1 Gallon Bottles	Item# 98PMV0G

Directions:

1. Floor must be completely clean, dry and free of any other floor maintenance products.
2. With a clean mop or applicator, apply 2-3 coats thin coats of MVP. Wait for each coat to dry before applying additional coats.
3. For best results, when finish is completely dry, buff final coat with high speed buffer with super soft non-aggressive pad. Once floor surface has been thoroughly coated, you may apply selected Protegé floor finish per directions.

First Aid:

Inhalation: Remove to fresh air. Skin: Wash with soap and water. Eyes: Flush with water for 15 minutes. If irritation persists, consult physician. Internal: If ingested, drink large amounts of water, induce vomiting. Seek medical attention promptly.

Storage:

Keep from freezing. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area.



**INNOVATIVE
CHEMICAL
CORPORATION**

7769 95th St. S, Cottage Grove, MN 55016
P:651.649.1762 TF:866.472.3932 F:651.649.1787
www.iccmn.com